

# BULLZCUT CNC CX- 3000E PVC LAMINATING MACHINE WITH PLC TOUCH SCREEN



## PRODUCT DESCRIPTION

This machine can be used for three-dimensional overlaying PVC, soft bag, Boeing film and plastic on the surface of wood, wood-based panel, aluminum alloy, steel plate, gypsum board and other materials (with our customized silica gel board, it can be overlaid with wood skin and heat transfer printing).

1. The use time of the electrical control part and the temperature control system of the electrical solenoid valve. The electrical control parts are made of CHINT electrical appliances with low failure rate. The microcomputer temperature meter automatically searches for the temperature change speed, so as to adjust the heating speed, so as to achieve the purpose of accurate temperature control.
2. Using aluminum heating system, heating evenly, high quality insulation material, saving energy and electricity.

## TECHNICAL PARAMETER

Dimensions	11000mm*2100mm*1800mm
Working Table Size	1100*3000mm 1300*3000mm (snowflake galvanized steel)0.03cm
Power	negative pressure>0.095MP
Temperature Heating	Metal five side aluminum heating + low heating (aluminum heating)
Voltage	380V
Power	30KW
Actual Consumption	10kw
Working Type	One key start + automatic in and out + timing heating + automatic covering
Control Switch	CHINT
Vacuum Pump	140m <sup>3</sup> / h vacuum negative pressure Vacuum pump 2.2kW + large capacity double gas tank

## APPLICABLE INDUSTRIES

It is an ideal auxiliary processing equipment for furniture, cabinet, decorative materials, artwork, acrylic, panel furniture, decorative skirting board and advertising speaker industry Equipment, low heating vacuum laminating machine, can do high gloss lamination, low heating softening degree is good, plastic effect is better, work efficiency is high, heating fast and uniform, forming fast, solid absorption, surface smooth but flat

## PRODUCT SAMPLE

